

Pneumatic Positioner type QS-P2G-LT-RE

- Direct Mounted, mechanical 90° feedback
- Operating alternatives; On/off, Ramp or Regulating
- No air consumption when not moving
- Visual position indicator
- Analogue input: 1, V or mA
- Manual function, open/close



TECHNICAL DATA

Air consumption at rest	No air consumption
Analogue input 1:	0/4-20 mA DC * 0/1-5VDC * 0/2-10VDC
Connection of electrical signals TB:1 (Ai/DC)	Quick Connector, 7-pole, FM, IP66
Connection of electrical signals TB:2 (Di/Do)	Quick Connector, 7-pole, M, IP66
Dew point/ Dust contentsupply air	< -40 °C/ < 30 um
Digital output	Only OEM version (NPN)
Enclosure	IP66
Material, housing	Cast aluminium, Powder coated
Supply pressure / Max flow	2-7 bar / 196 L/min
Supply voltage standard version "B0"	24 VDC +/-10%
Temperature limits	-25...+70°C
Threaded connection air supply	R 1/8"
Threaded connection positioner to actuator	R 1/4"
Weight	App. 1,6kg
CE Directives	EMC: EN50 081-2, EN50 082-2

OPTIONS

- Actual position, mA out
- Contactless external feedback (Linear & Rotary)
- Fail safe stop, open, close
- Limit switches 2Pcs (External)
- PosiForce™ for ball & throttle valve, optimizing control range
- PosiTight™ to secure closed position for single acting actuators
- Quick connector IP66 for all electrical connections

DIMENSIONS (mm)

