



Strainer PN 25/40 Y-type, with flanged ends and drain-plug 1/2" in cover

Materials: Body: GS-C 25, Screen: stainless steel 1.4301, Gasket: graphit reinforced

Connection: flanged ends DIN

Test pressure: 60 bar

DN	L	A	Mesh-width*	Weight (kg)	Article-Number**
15	130	75	0,50	2,50	20325015
20	150	75	0,50	3,00	20325020
25	160	90	0,87	4,00	20325025
32	180	90	0,87	5,00	20325032
40	200	110	0,87	7,00	20325040
50	230	120	0,87	11,00	20325050
65	290	140	0,87	18,00	20325065
80	310	165	1,32	23,00	20325080
100	350	220	1,32	31,00	20325100
125	400	260	1,32	48,00	20325125
150	480	300	1,32	61,00	20325150
200	600	360	1,32	153,00	20340200

* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

** When ordering with fine screen: Article-Nr. + addition with F-SIEB

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	Ø G	Ø R	P	D	B
15	62	22,5	39%	2,70	2,50	2,14	2,50	39	27	1,5	40x98 oval	120
20	62	22,5	39%	8,80	7,10	2,14	2,50	39	27	1,5	40x98 oval	125
25	86	35	38%	16,90	15,50	2,14	2,55	62	47	1,5	48x78 oval	150
32	86	35	38%	25,00	20,60	2,58	3,87	56	40	1,5	54x89 oval	170
40	98	45	38%	38,00	33,20	2,83	3,67	68	51	1,5	70x72	205
50	111	55	38%	56,00	47,50	3,11	4,36	84	58	1,5	91x95	250
65	121	63	38%	89,00	72,70	3,51	5,28	95	71	1,5	100x110	285
80	137	77	38%	127,00	96,80	4,02	6,90	122	98	2,00	121x131	330
100	169	100	36%	200,00	167,00	3,92	5,63	137	115	2,00	137x145	415
125	198	120	36%	332,00	284,00	3,49	4,77	172	146	2,00	175x190	484
150	239	150	36%	494,00	389,00	3,26	5,26	220	180	2,00	Ø 306	535
200	290	186	36%	675,00	570,00	5,50	7,60	260	212	2,0	Ø 345	720