



## Strainer PN 16 Y-type, with flanged ends and drain-plug 1/2" in cover

**Materials:** Body: nodular cast iron JS 1030, Screen: stainless steel 1.4301 (from DN 150 perforated plate 1.4301), Gasket: graphit reinforced

**Connection:** flanged ends DIN

**Test pressure:** 24 bar

DN	L	A	Mesh-width*	Weight (kg)	Article-Number**
65	290	140	0,75	9,60	96906516
100	350	220	1,20	22,00	96910016
125	400	260	1,20	34,00	96912516
150	480	300	1,20	48,50	96915016
200	600	360	1,20	111,00	96920016
250	730	550	1,20	220,00	96925016
300	850	610	1,20	272,00	96930016

\* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

\*\* When ordering with fine screen: Article-Nr. + addition with F-SIEB

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	Ø G	Ø R	P	D	B
65	123	73	38%	119,50	105,40	2,00	2,57	94	83	1,0	111x111	220
100	184	108	36%	217,50	196,70	3,38	4,14	134	120	1,0	Ø 194	340
125	219	135	36%	364,40	320,00	2,94	3,81	158	138	1,5	Ø 234	410
150	258,5	160	36%	537,00	468,00	2,81	3,70	180	162	1,5	Ø 264	475
200	360	208	36%	820,00	769,00	3,81	4,33	240	209	2,0	Ø 290	580
250	336	231	35%	1260,00	1108,00	3,94	5,09	319	275	2,0	Ø 345	830
300	386	281,5	35%	1735,00	1520,00	4,31	5,61	379	320	2,0	Ø 401	950