



## Strainer PN 100, Y-type with welded flanges and drain-plug in cover

**Materials:** Body and flanges: forged steel C22, Screen: perforated plate Stainless steel 1.4301,  
 Gasket: graphit reinforced

**Connection:** flanged ends DIN

**Test pressure:** 205 bar

DN	L	A	Mesh-width*	Weight (kg)	Article-Number**
1/2"	210	60	0,8	12,00	0206040801500
3/4"	230	75	0,8	13,00	0206040802000
1"	230	85	0,8	16,00	0206040802500
1 1/4"	260	120	0,8	25,00	0206040803200
1 1/2"	260	120	0,8	29,00	0206040804000
2"	230	160	0,8	43,00	0206040805000

\* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

\*\* When ordering with fine screen: Article-Nr. + addition with F-SIEB

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	Ø G	Ø R	P	D	B
1/2"	41	18	38%	5,1	5,0	1,56	1,60	36	29	3,5	1/4"	85
3/4"	60	22	38%	9,7	9,6	2,22	2,27	40	33	3,5	1/4"	135
1"	75	28	38%	14,6	13,3	3,07	3,71	50	41	3,5	1/4"	170
1 1/4"	110	41	38%	32,6	29,9	3,84	4,52	74	57	3,5	1/4"	230
1 1/2"	110	41	38%	32,6	29,9	3,84	4,52	74	57	3,5	1/4"	230
2"	123	55	38%	50,3	49,8	3,84	3,92	79	66	3,5	1/4"	240