



## Strainer PN 160 Y-type, with flanged ends and drain-plug 1/2" in cover

**Materials:** Body: CrMo55, Screen: stainless steel 1.4301

**Connection:** flanged ends DIN

**Test pressure:** 240 bar

| DN  | L   | A   | Mesh-width* | Weight (kg) | Article-Number** |
|-----|-----|-----|-------------|-------------|------------------|
| 15  | 210 | 130 | 1,00        |             | 0206041301502    |
| 20  | 220 | 130 | 1,00        |             | 0206041302002    |
| 25  | 230 | 140 | 1,00        |             | 0206041302502    |
| 32  | 250 | 160 | 1,00        |             | 0206041303202    |
| 40  | 260 | 190 | 1,00        |             | 0206041304002    |
| 50  | 300 | 205 | 1,00        |             | 0206041305002    |
| 65  | 340 | 230 | 1,00        |             | 0206041306502    |
| 80  | 380 | 240 | 1,00        |             | 0206041308002    |
| 100 | 430 | 270 | 1,00        |             | 0206041310002    |
| 125 | 500 | 335 | 1,50        |             | 0206041312502    |
| 150 | 550 | 375 | 1,50        |             | 0206041315002    |
| 200 | 650 | 460 | 1,50        |             | 0206041320002    |

\* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

\*\* When ordering with fine screen: Article-Nr. + addition with F-SIEB

| DN  | L1  | D1  | Fo  | KVS1 | KVS2 | Zet1 | Zet2 | Ø G | Ø R | P   | D | B |
|-----|-----|-----|-----|------|------|------|------|-----|-----|-----|---|---|
| 15  | 100 | 25  | 36% |      |      |      |      | 60  | 49  | 1,5 |   |   |
| 20  | 103 | 30  | 36% |      |      |      |      | 60  | 49  | 1,5 |   |   |
| 25  | 105 | 32  | 36% |      |      |      |      | 60  | 49  | 1,5 |   |   |
| 32  | 118 | 40  | 36% |      |      |      |      | 70  | 49  | 1,5 |   |   |
| 40  | 135 | 50  | 36% |      |      |      |      | 82  | 68  | 1,5 |   |   |
| 50  | 158 | 60  | 36% |      |      |      |      | 82  | 68  | 1,5 |   |   |
| 65  | 170 | 75  | 36% |      |      |      |      | 110 | 94  | 1,5 |   |   |
| 80  | 182 | 90  | 36% |      |      |      |      | 110 | 98  | 1,5 |   |   |
| 100 | 225 | 110 | 36% |      |      |      |      | 145 | 125 | 1,5 |   |   |
| 125 | 238 | 135 | 36% |      |      |      |      | 190 | 170 | 1,5 |   |   |
| 150 | 300 | 160 | 36% |      |      |      |      | 210 | 190 | 1,5 |   |   |
| 200 | 361 | 210 | 36% |      |      |      |      | 265 | 245 | 1,5 |   |   |