



Strainer PN 40 Y-type welded construction, with flanged ends and drain-plug 1/2" in cover

Materials: Body: S355J2H, Cover: P265GH, Flanges: G235JRG2, Screen: stainless steel 1.4301, Gasket: graphite reinforced

Connection: flanged ends EN 1092-1

Test pressure: 60 bar

DN	L	A	Mesh-width*	Weight (kg)	Article-Number**
200	600	580	2,00	145	0406040620000
250	730	600	2,00	239	0406040625000
300	850	620	2,00	336	0406040630000
350	980	640	3,00	439	0406040635000
400	1100	750	3,00	602	0406040640000
450	1200	850	3,00	700	0406040645000
500	1250	875	3,00	801	0406040650000
600	1450	900	4,00	1004	0406040660000
700	1650	1200	4,00		0406040670000
800	1850	1400	4,00		0406040680000

* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

** When ordering with fine screen: Article-Nr. + addition with F-SIEB

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	Ø G	Ø R	P	D	B
200					700		5	290	200	2	3/4" BSP	900
250					1100		5	250	352	2	3/4" BSP	1000
300					1500		5,5	417	300	2	1" BSP	1050
350					2000		6	474	350	2	1" BSP	1100
400					2500		6,5	546	400	2	1" BSP	1250
450					3200		6,5			2	1" BSP	1500
500					3900		6,5	628	500	2	1" BSP	1500
600					5600		6,5			2	1" BSP	1700
700											1" BSP	
800											1" BSP	