



Strainer PN 40 Y-type, with screwed ends

Materials: Body: stainless steel 1.4408, Screen: stainless steel perforated plate 1.4408 Gasket: PTFE

Connection: screwed ends BSP

Test pressure: 60 bar

DN	L	A	Mesh-width*	Weight (kg)	Article-Number**
3/8"	57	32	1,00	0,22	0306010603800
1/2"	61	37	1,00	0,35	0306010601200
3/4"	70	41	1,00	0,40	0306010603400
1"	86	47	1,00	0,55	0306010604400
1 1/4"	100	55	1,00	0,90	0306010605400
1 1/2"	111	62	1,00	1,10	0306010606400
2"	138	76	1,00	1,60	0306010608400

* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

** When ordering with fine screen: Article-Nr. + addition with F-SIEB

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	Ø G	Ø R	P	D	B
3/8"	26	12	37%	2,70	2,50	2,14	2,50	23,0	20,6	1,1		34
1/2"	32	17	37%	5,10	5,00	1,56	1,60	27,0	25,0	1,1		40
3/4"	36	21	37%	9,70	9,60	2,22	2,27	31,5	28,0	1,2		45
1"	46	28	37%	14,60	13,30	3,07	3,71	38,5	36,5	1,2		55
1 1/4"	54	32	37%	32,60	23,50	2,96	2,99	46,0	43,0	1,3		63
1 1/2"	62	40	37%	32,10	29,90	3,84	4,52	53,5	49,0	1,5		70
2"	78	52	37%	50,3	49,80	3,84	3,92	68,0	63,5	1,5		87