



## Strainer PN 25 Y-type, with flanged ends and drain-plug 1/2" in cover

**Materials:** Body: nodular cast iron JS 1030, Screen: stainless steel 1.4301 (from DN 150 perforated plate 1.4301), Gasket: graphit reinforced

**Connection:** flanged ends DIN

**Test pressure:** 37,5 bar

**Specials:** Epoxy paint (wet)inside + outside  
 RAL 5005, 100-150 microns.

DN	L	A	Mesh-width*	Weight (kg)	Article-Number**
15	130	75	0,50	2,00	9690152502
20	150	75	0,50	2,00	9690202502
25	160	90	0,75	3,00	9690252502
32	180	90	0,75	4,00	9690322502
40	200	110	0,75	5,90	9690402502
50	230	120	0,75	6,00	9690502502
65	290	140	0,75	9,60	9690652502
80	310	165	1,20	14,00	9690802502
100	350	220	1,20	22,00	9691002502
125	400	260	1,20	34,00	9691252502
150	480	300	1,20	48,50	9691502502
200	600	360	1,20	111,00	9692002502
250	730	550	1,20	220,00	9692502502
300	850	610	1,20	272,00	9693002502

\* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

\*\* When ordering with fine screen: Article-Nr. + addition with F-SIEB

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	Ø G	Ø R	P	D	B
15	53	25	39%	5,60	5,50	2,58	2,68	49	40	1,0	70x70	115
20	53	25	39%	10,70	10,30	2,24	2,41	49	40	1,0	70x70	115
25	66	31	38%	17,60	16,26	2,02	2,6	55	46	1,0	75x75	135
32	71	38	38%	29,15	26,60	1,97	2,37	55	46	1,0	75x75	135
40	91	47	38%	46,10	41,80	1,93	2,34	67	56	1,0	90x90	170
50	105	57	38%	71,60	63,70	1,95	2,46	74	66	1,0	98x98	190
65	123	73	38%	119,50	105,40	2,00	2,57	94	83	1,0	111x111	220
80	144	88	36%	173,50	144,00	2,18	3,16	109	100	1,0	136x136	265
100	184	108	36%	217,50	196,70	3,38	4,14	134	120	1,0	Ø 194	340
125	219	135	36%	364,40	320,00	2,94	3,81	158	138	1,5	Ø 234	410
150	258,5	160	36%	537,00	468,00	2,81	3,70	180	162	1,5	Ø 264	475
200	360	208	36%	820,00	769,00	3,81	4,33	240	209	2,0	Ø 290	580
250	336	231	35%	1260,00	1108,00	3,94	5,09	319	275	2,0	Ø 345	830
300	386	281,5	35%	1735,00	1520,00	4,31	5,61	379	320	2,0	Ø 401	950