



Strainer PN 10 T-type welded construction, with flanged ends and drain-plug 1/2" in cover

Materials: Body: S355J2H, Cover: P265GH, Flanges: G235JRG2, Screen: stainless steel 1.4301, Gasket: graphite reinforced

Connection: flanged ends EN 1092-1

Test pressure: 15 bar

DN	L	A	Mesh-width*	Weight (kg)	Article-Number**
200	600	300	3,00		0418040320000
250	730	350	3,00	167	0418040325000
300	850	400	3,00	226	0418040330000
350	980	450	5,00	294	0418040335000
400	1100	500	5,00	390	0418040340000
450	1200	600	5,00	424	0418040345000
500	1250	600	5,00	617	0418040350000
600	1450	700	5,00	837	0418040360000
700	1650	700	5,00		0418040370000
800	1850	800	5,00		0418040380000

* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

** When ordering with fine screen: Article-Nr. + addition with F-SIEB

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	Ø G	Ø R	P	D	B
200											1" BSP	
250			108	1300		3,50		378	300	2,00	1" BSP	600
300			126	1600		3,50		438	350	2,00	1" BSP	800
350			168	2500		3,50		490	400	2,00	1" BSP	900
400			210	3200		3,50		594	500	2,00	1" BSP	1000
450			236,25	4500		3,50		594	500	2,00	1" BSP	1100
500			283,50	5000		3,50		695	600	2,00	1" BSP	1100
600			367,50	7500		3,20		810	700	2,00	1" BSP	1300
700											1" BSP	
800											1" BSP	