



Strainer PN 10 Y-type welded construction, with flanged ends and drain-plug 1/2" in cover

Materials: Body: S355J2H, Cover: P265GH, Flanges: G235JRG2, Screen: stainless steel 1.4301, Gasket: graphite reinforced

Connection: flanged ends EN 1092-1

Test pressure: 15 bar

DN	L	A	Mesh-width*	Weight (kg)	Article-Number**
200	600	580	2,00	95	0406040320000
250	730	600	2,00	146	0406040325000
300	850	620	2,00	196	0406040330000
350	980	640	3,00	243	0406040335000
400	1100	750	3,00	304	0406040340000
450	1200	850	3,00	398	0406040345000
500	1250	875	3,00	466	0406040350000
600	1450	900	4,00	614	0406040360000
700	1650	1200	4,00		0406040370000
800	1850	1400	4,00		0406040380000

* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

** When ordering with fine screen: Article-Nr. + addition with F-SIEB

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	Ø G	Ø R	P	D	B
200					700		5	293	200	2	3/4" BSP	900
250					1100		5	328	250	2	3/4" BSP	1000
300					1500		5,5	378	300	2	1" BSP	1050
350					2000		6	438	350	2	1" BSP	1100
400					2500		6,5	489	400	2	1" BSP	1250
450					3200		6,5	539	450	2	1" BSP	1500
500					3900		6,5	594	500	2	1" BSP	1500
600					5600		6,5	695	600	2	1" BSP	1700
700											1" BSP	
800											1" BSP	