



DRV 750
 Type A (DN 15 - DN 32)



DRV 750
 Type B (DN 40 - DN 80)



Pressure reducing valve
Female thread • Low pressure
Stainless steel

Pressure reducing valves of the series are diaphragm-controlled, spring-loaded pressure reducing valves. These valves are inlet pressure relieved.

DGRL 2014/68/EU



Classification societies

- DNV GL
- LR
- BV
- ABS
- CCS

Customs tariff number

84811005

Media

The pressure reducers are suitable for use with aggressive waters and other aggressive liquids, but can also be used for air and neutral gases when larger flow rates are required.

FDA / EC 1935/2004

Our stainless steel series with EPDM seals correspond to the requirements of the EU Regulation EC 1935/2004 and the Regulations of the FDA (Food and Drug Administration).

The metallic components in contact with the medium are made of austenitic materials such as 1.4408 and 1.4404.

The EPDM seals are conform FDA (21 CFR part 177.2600) and EC 1935/2004. This means you can use our stainless steel series with EPDM seals in food applications without hesitation.



Features

- pressure-relieved single seated valve
- diaphragm-controlled
- continuously adjustable outlet pressure
- max. inlet pressure up to 25 bar
- outlet pressure : 0,2 - 2 bar
- female thread acc. ISO 228, optionally with NPT-Gewinde
- with integrated strainer filter
- replaceable inner parts
- double-ended G 1/4" manometer fitting (for outlet pressure)
- assembly position: any desired, preferably vertical
- minimum pressure difference (inlet/outlet pressure): 1 bar
- EPDM seals with FDA conformity

Pressures



max. 25 bar



0,2 - 2 bar

Connections



Female thread
 acc. ISO 228
 from G 1/2" up to G 2"

Materials

	body	spring bonnet	seals	wetted parts	max. temperature
standard version	stainless steel 1.4408	stainless steel 1.4408	FKM optionally EPDM*, NBR***	stainless steel 1.4404	190 °C**



temperatures

Various options in the area of seals and wetted internal parts allow a maximum temperature of up to 190°C.



from -30 °C up to +190 °C

Seals and temperatures

NBR***	-15°C to +100°C
EPDM*	-30°C to +130°C
FKM	-10°C to +190°C

* with FDA conformity
 ** with FKM seals
 ***only DN 15 to DN 32



Technical data

nominal size	15	20	25	32	40	50
G	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"

Type
Pressures

max. 25 bar



max. inlet pressure [bar]

DRV 750

A

25

B

25

0,2 - 2 bar



outlet pressure [bar]

DRV 750

0,2 - 2

0,2 - 2

Connections

Female thread
 from G 1/2" to G 2"



dimensions [mm]

	G	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
DRV 750	b	95	95	110	120	150	160
	h1	29	29	38	38	38	38
	h	136	136	148	148	271	271

weight [kg]

DRV 750	1,8	1,7	3,1	3,1	9,1	9,0
---------	-----	-----	-----	-----	-----	-----

kvs-value [m³/h]

DRV 750	2,9	3,9	5,4	6,1	9	13
---------	-----	-----	-----	-----	---	----

