



DRV 730-D-R



DRV 730-D-R
Type A (DN 15 - DN 32)



DRV 730-D-R
Type B (DN 40 - DN 50)



Media

The pressure reducers are particularly suitable for use with hot water and steam, but can also be used in the case of aggressive water and other aggressive liquids. They are also suitable for air and neutral gases when larger flow rates are required.

Pressure reducing valve Male thread • Steam Stainless steel

Pressure reducing valves of the series are piston-controlled, spring-loaded pressure reducing valves. These valves are inlet pressure relieved.

DGRL 2014/68/EU



Classification societies

- DNV GL
- LR
- BV
- ABS
- CCS

Customs tariff number

84811019



Features

- pressure relieved single seated valve
- piston-controlled
- continuously adjustable outlet pressure
- max. inlet pressure up to 16 bar
- outlet pressure: 0.3 - 2 bar
- male thread acc. ISO 7
- replaceable inner parts
- double-ended G 1/4" manometer fitting (for outlet pressure)
- assembly position: any desired, preferably vertical
- minimum pressure difference (inlet/outlet pressure): 0.3 bar



Temperatures

Various options in the area of seals and wetted inner parts allow a maximum temperature of up to 200 °C.



from -30 °C up to +200 °C

Seals and temperatures

PTFE/ EPDM	- 30 °C to +150 °C
PTFE/ EPDM/ FEPM	+20 °C to +200 °C

Pressures



max. 16 bar



0,3 - 2 bar

Connections



Male thread
acc. ISO 7
from R 1/2" up to R 2"

Materials

	body	spring bonnet	seals	wetted inner parts	max. temperature
	steam up to 150 °C	stainless steel 1.4408	PTFE/ EPDM	stainless steel 1.4404	150 °C
	steam up to 200 °C	stainless steel 1.4408	PTFE/ EPDM/ FEPM	stainless steel 1.4404	200 °C

DRV 730-D-R



Technical data

nominal size R	15	20	25	32	40	50
	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"

Type

Pressures

max. 16 bar



max. inlet pressure [bar]

DRV 730-D-R

A

B

16

16

outlet pressure [bar]



0.3 - 2 bar

DRV 730-D-R

0.3 - 2

0.3 - 2

Connections

male thread
from R 1/2" up to R 2"



dimensions [mm]


	R	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
DRV	b	105	105	122	122	156	160
730-D-R	b1	168	168	195	195	250	250
	h1	29	29	38	38	38	38
	h	150	150	151	151	260	260

weight [kg]

DRV 730-D-R	2.6	2.6	3.7	3.8	8.7	9.8
-------------	-----	-----	-----	-----	-----	-----


kvs-value [m^3/h]

all types	3.0	3.3	4.5	4.7	11.3	12.0
-----------	-----	-----	-----	-----	------	------






Sizing Step 1: Valve capacity



Example: Selection of a valve for an inlet pressure (p_1) of 2.4 and an outlet pressure (p_2) of 1.4 bar based on the valve capacity. The application requires a saturated steam mass flow of 300 kg/h. Dimensioning according to the maximum flow rate: Entering the criteria shows that a DN40 valve would be sufficient (the required capacity to the left of the dashed line).

Sizing Step 2: Max. Flow rate



Example: Selection of a valve for an inlet pressure (p_1) of 2.4 and an outlet pressure (p_2) of 1.4 bar based on the maximum recommended media velocity of 40 m/s. The application requires a saturated steam mass flow of 300 kg/h. Dimensioning according to the maximum media velocity: Entering the criteria shows that a DN50 valve would be sufficient (curve above the required capacity).

Manometer

diameter	connection	body	pressure range	max. temp.	art.no.*
63 mm	G 1/4", central back	stainless steel	0 - 10 bar	200 °C	009014

*article numbers are 11 digits, see option overview and configuration example